


28th August 2017



HELP YOUR BUSY NEIGHBOURS
DYNAMIC MULTICASTS
OVER STATIC TOPOLOGIES

Robert Kuban, Randolf Rotta, Jörg Nolte

Distributed Systems / Operating Systems

OUR TARGET SCENARIO



Brandenburg
University of Technology
Cottbus - Senftenberg

objective: scalable multicasts

- + acknowledgement of completion
- + dynamic group membership (join/leave)

applications: cache invalidation, esp. TLB shutdown

hardware: many-cores like Intel XeonPhi, Tilera TilePro...


- + cache-coherent shared memory
- + point-to-point message passing

EXAMPLE: LINUX TLB SHOOTDOWN

Linux 4.11 x86 smp_call_function_many ()

Initiator (Sender)

1. update page tables
2. enqueue invalidation tasklet at each thread
3. send IPI to each thread
4. wait on flag in each tasklet



Other CPU Threads

IPI handler processes tasklet:


1. invalidate page(s) in TLB
2. set ACK flag in tasklet

⇒ flat topology

👍 fast join/leave via bit-mask

👎 $\mathcal{O}(n)$ latency

EXAMPLE: MULTICASTS IN BARRELFISH



- propagate along a **tree topology**
- use constraint solver for optimized topology
- proposed for TLB shutdowns¹

🚫 expensive join/leave or interrupt ex-members




👍 $\mathcal{O}(\log n)$ latency

¹Baumann et al., *The multikernel: A new OS architecture for scalable multicore systems*, 2009



DESIGN SPACE

Multicasts (just members)



Flat




-  low latency
for small groups
-  high latency
for large groups
-  fast join/leave

Tree

-  always low latency
-  costly join/leave

Broadcasts (over all threads)

-  always high latency
-  interrupts non-members

-  good latency
for large groups
-  bad latency
for small groups
-  interrupts non-members

Problem Statement: Combine...


- fast join/leave like with flat topology
- low latency like in tree topologies (parallel propagation)

Solution Idea

- use **static tree topology** like in broadcasts (can be hand-crafted for the processor)
- membership as **bit-mask** for fast join/leave
- exploit shared memory to **skip non-members**, just message passing to actual members

SOLUTION: HELPING


Skip non-member scatter nodes




Setup

- Intel XeonPhi Knights Corner (1.053 GHz)
- 60 cores
- message passing via shared memory
- polling

Flat Topology




Binary Tree




FLAT TOPOLOGY

multicast similar to Linux TLB shutdown




FLAT TOPOLOGY WITH HELPING

Overhead from membership tests and graph traversal



BINARY TREE WITH HELPING, SKIPPING



Scalable, acknowledged, dynamic multicasts for manycores:

Challenges: generating good topologies is costly,
flat topology not scalable,
non-members should not be interrupted

Solution: static optimized broadcast topology,
help and skip non-member cores


Result: success for large groups, alright for small

Implications: improve Linux TLB shutdown for Many-Core HPC apps


ACKNOWLEDGE VIA SHARED MEMORY

Decrement shared variable instead of message passing

Only message passing:




Using shared memory:



HELPING WITH SHARED MEM ACK

→ tree combining² for gather nodes



¹Yew et al., *Distributing Hot-Spot Addressing in Large-Scale Multiprocessors*, 1987